



Heavy Duty Diesel Engine Oils

SAE 10W, SAE 30, SAE 40

Heavy Duty Diesel Engine Oils

Benefits:

- Fortified with advanced technology detergents, dispersants, anti-wear, and anti-corrosion additives.
- Provides protection against engine sludge, varnish formation, high temperature oil thickening, scuffing and wear.

Applications:

- Fit for use in: API Service Categories CF, CF-2/SG, Ford M2C153-C, Caterpillar Series 3, Mack EO-K, MIL-L-2104C, Detroit Diesel Corporation Series 53, 71 & 92 two stroke cycle diesel engines (7193, 7194)
- SAE 10W (7191) meets only API category CF

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200



SAE Grade	Test Method	10W	30	40
API Service		CF	CF, CF-2/SG	CF, CF-2/SG
API Gravity, 60°F	ASTM D-4052	30.8	27.8	26.2
Density, lbs/gal (g/L)	Calculated	7.26 (870)	7.40 (887)	7.47 (895)
Viscosity, cSt @ 40°C	ASTM D-445	36.5	93.3	153.6
Viscosity, cSt @ 100°C	ASTM D-445	6.6	11.3	15.5
Viscosity Index	ASTM D-2270	124	107	103
CCS @ -25°C, cP	ASTM D-5293	3,800	N/A	N/A
MRV @ -30°C, cP	ASTM D-4684	12,225	N/A	N/A
Pour Point, °F (°C)	ASTM D-5949	-33 (-36)	-22 (-30)	-11 (-24)
Flash Point, °F (°C)	ASTM D-92	365 (184)	420 (216)	450 (232)
Color	ASTM D-1500	3.0	5.0	5.0
TBN	ASTM D-2896	9.0	7.2	7.2
Sulfated Ash, wt. %	ASTM D-874	1.20	0.95	0.95
Product Code		7191	7193	7194

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

