



Universal Tractor Fluid

Universal Tractor Fluid

Benefits:

- Provides year round protection
- Outstanding low temperature performance
- Resistance to high-temperature oxidation.
- Prevents brake chatter (controlled frictional properties)
- Exceptional anti-wear protection
- Superior rust and corrosion protection
- Outstanding system cleanliness

Applications:

Formulated to meet or exceed the requirements of agricultural, construction and forest products equipment where a single fluid is used to lubricate hydrostatic drives, mechanical (manual) transmissions, hydraulic systems, wet brakes, gear drives and axles, power take-offs (PTO) and power steering mechanisms.

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200



	Test Method	
API Service		GL-4
Gravity, API	ASTM D-4052	30.1
Density, lbs/gal (g/L)	Calculated	7.29 (875)
Viscosity, cSt @ 40°C	ASTM D-445	58.2
Viscosity, cSt @ 100°C	ASTM D-445	9.3
Viscosity Index	ASTM D-2270	141
Brookfield Viscosity, cP @ -18 °C	ASTM D-2983	2,900
Brookfield Viscosity, cP @ -34.4 °C	ASTM D-2983	60,000
Pour Point, °F (°C)	ASTM D-5949	-38 (-39)
Flash Point, °F (°C)	ASTM D-92	400 (204)
Color	ASTM D-1500	2.5
Product Code		7352

TRACTOR OEMs

AGCO:

AGCO-Allis

Power Fluid 821XL

ACGO-Chalmers

Power Fluid 821

Deutz-Allis

272843, 257541, 246634

Massey-Ferguson

M-1135, M-1141, M-1145,
M-1143, M-1129A, M-1110,
M-1127A, M-1127B

White Farm

Q-1826

Minneapolis-Moline

Q-1766, Q-1722, Q-1766B

Oliver

Q-1705

New Idea

Q-1802, Type 55

ZF

TE-ML 03E, TE-ML 03F,

TE-ML 05F, 05E, TE-ML 06K

CNH Global N.V.:

Case International

MS-1206, MS 1207 (Hy-Tran Plus)

CNH MS-1209*

Case-IH

MS-1210 / JIC 145 (TCH)

JI Case

JIC 143 / 144

International Farmall

MS-1204, JIC 185

International Harvester

B-5, B-6

Steiger

SEMS 17001

New Holland (Fiat)

Ford and New Holland

MAT 3525, FNHA-2-C-201

MAT 3526

FNHA-2-C-200

FNHA-2-C-200A

ESN-M2C41-B, M2C43,

M2C48-A, M2C48-B,

M2C53-A, M2C53-B, M2C92-A,

M2C134-A, B, C, D (Current)

35VQ25, M-2952-S (Vickers)

Kubota

UDT

Sperry-Vickers

I-286-S (Vickers)

M-2950-S (Vickers)

Versatile

Specification 23M or 24M

Hesston-Fiat (tractors only):

AF-87, Multi-F, Multi-G

Volvo CE

WB 101

John Deere

JDM J20C (Hygard)

JDM J20D (#7351 only)

JDM J20A, J20B, J14B, J14C,

JDM J21A, JDT 303, Quatrol

Komatsu Dresser

B-06-0001, B-06-0002

Renk Doromat

873, 874 A, 874 B

TRANSMISSION OEMs:

Caterpillar TO-2

Allison C-2, C-3

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

