

VEEDOL SINTRON LongLife III 5W-30

Description

Veedol Sintron LongLife III 5W-30 is a fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- · a lower fuel consumption
- · low SAPS content
- · suitable for modern catalysts
- · a fast cold start
- · a safe lubrication film at high temperatures
- · extended oil drain intervals
- · a very good detergency and dispersion
- · a very strong protection against wear, corrosion and foaming

Features & Benefits

Veedol Sintron LongLife III 5W-30 is a specially composed motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the latest VW 504.00/507.00 requirements, in practice also called VW Longlife III oils.

Performance Specifications

ACEA C3 MB-Approval 229.51 Approved under VW 504.00/507.00 BMW Longlife-04 Porsche C30

Typical Properties

Density at 15°C, kg/l	351
Viscosity -30°C, mPa.s59	950
Viscosity 40°C, mm²/s	,20
Viscosity 100°C, mm²/s	,00
Viscosity Index	171
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	6,7
Sulphate Ash, % 0	,67

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

[™] Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.